



# FORMPLUS

## Joint Sealing

### **FORMSHIELD PREMIUM**

#### **Concrete Plant & Formwork Protector**

**FORMSHIELD PREMIUM** displaces water and leaves behind a dry flexible well bonded waxy protective coating which:

- Is a highly effective corrosion inhibitor for metal components for use during storage and transportation.
- Eases removal of subsequent concrete build-up on equipment.
- Disperses water from surfaces
- Easily applied by dipping, spray, brush or roller

**FORMSHIELD PREMIUM** is a special blend of corrosion inhibiting agents and petroleum distillates developed to be easy to use and to give maximum protection to metal surfaces where prolonged storage and shipping is envisaged.

The material is also a highly efficient release agent that facilitates the removal of concrete from metal surfaces, making it ideal for use during cleaning and refretting operation of equipment in constant use.

- Protects expensive plant and formwork from corrosion
- Non-acidic safe to use on all plant, metal, rubber, plastic etc.
- Saves time and money in the cleaning up operation after use.

#### **Instruction for use**

**FORMSHIELD PREMIUM** can be used to treat new and used equipment.

#### **Preparation**

All existing contamination should be carefully removed preferably using **FORMCLEAN** on hardened concrete. The equipment should then be washed off thoroughly with clean water.

#### **Application**

For best results objects may be dipped into **FORMSHIELD PREMIUM** and lightly agitated. However, where this is not practicable then **FORMSHIELD PREMIUM** should be applied as a single thin coat using a spray, brush, or roller, in a well ventilated area.

#### **Cleaning up**

Application equipment and unwanted splashes should be cleaned using **RESOFORMKLENS**. The material is touch dry within 4 hours at 20°C

#### **Physical data**

**FORMSHIELD PREMIUM** is a pale coloured liquid with the characteristic odour of petroleum distillates. The material is flammable with a Flash Point of 42°C and should be stored and used accordingly. Containers should be sealed after use to prevent evaporation.

#### **Health and safety**

The material is non-toxic but should not be ingested.

Eyes should be protected from splashes and all reasonable precautions taken to prevent undue exposure.

If eyes are affected by splashes then wash with copious quantities of clean water and seek medical advice.

**formworkdirect.co.uk**  
TEL:  
(+44) (0)151 532 0179  
EMAIL  
sales@formworkdirect.co.uk



**formworkdirectmalta.com**  
TEL:  
+356 2124 4241  
EMAIL  
formworkdirect@polidano-group.com