



FORMPLUS

Joint Sealing

FORMFLOW 2000

Standard Set Plasticiser

The addition of **FORMFLOW 2000** to an existing concrete mix facilitates up to 25% reduction in added water content for a given slump with the resultant marked reduction in water/cement ratio providing increased strengths.

Alternatively it will increase slump by up to 150% without any increase in water content.

Composition

A concentrated aqueous solution of lignin based water reducing agent containing no chlorides or nitrates.

Cement Economy

A concrete mix, designed to provide a specific compressive strength might be substantially reduced in cost by redesigning with the inclusion of **FORMFLOW 2000**.

Specification Clause

FORMFLOW 2000 Standard Setting Plasticiser manufactured by **FORMWORK DIRECT** shall be added to the concrete mix in accordance with the manufacturer's recommendations.

Storage

Protect from freezing. In the event of freezing, material should be completely thawed and then thoroughly mixed before use.

Health & Safety

FORMFLOW 2000 is non toxic and non-flammable. Any splashes should be washed with water, if contact with eyes occurs wash thoroughly with water. If irritation persists seek medical advice.

Refer to separate **FORMFLOW 2000** Health and Safety leaflet.

formworkdirect.co.uk
TEL:
(+44) (0)151 532 0179
EMAIL
sales@formworkdirect.co.uk



formworkdirectmalta.com
TEL:
00356 255 85322
EMAIL
formworkdirect@polidano-group.com