



# FORMPLUS

## Joint Sealing

### FORMFLOW2000-ST

#### Standard Set Plasticiser

The addition of **FORMFLOW 2000-ST** to an existing concrete mix facilitates up to 25% reduction in added water content for a given slump with the resultant marked reduction in water/cement ratio providing increased strengths.

Alternatively it will increase slump by up to 150% without any increase in water content.

#### Composition

A concentrated aqueous solution of lignin based water reducing agent containing no chlorides or nitrates.

#### Cement Economy

A concrete mix, designed to provide a specific compressive strength might be substantially reduced in cost by redesigning with the inclusion of **FORMFLOW 2000-ST**.

#### Specification Clause

**FORMFLOW 2000-ST** Standard Setting Plasticiser manufactured by **FDI LTD** shall be added to the concrete mix in accordance with the manufacturer's recommendations.

#### Storage

Protect from freezing. In the event of freezing, material should be completely thawed and then thoroughly mixed before use.

#### Health & Safety

**FORMFLOW 2000-ST** is non toxic and non-flammable. Any splashes should be washed with water, if contact with eyes occurs wash thoroughly with water. If irritation persists seek medical advice.

Refer to separate **FORMFLOW 2000-ST** Health and Safety leaflet.

**formworkdirect.co.uk**  
TEL:  
(+44) (0)151 532 0179  
EMAIL  
sales@formworkdirect.co.uk



**formworkdirectmalta.com**  
TEL:  
+356 2124 4241  
EMAIL  
formworkdirect@polidano-group.com