



FORMCAST

Precasting Release Agents

FORMSTRIKE EXTRA 402S

Concrete Mould Oil (BCA Category 2)

Description

FORMSTRIKE EXTRA 402S is a specially blended, highly versatile, quality neat oil with surfactant which is ideal for use on metal, timber, other formwork materials and coatings. It has been formulated to give an optimum release of formwork and high quality of finish to concrete over a wide range of mix designs.

Benefits

- Effective, clean, positive release, reducing labour costs, cleaning time and possible damage to formwork.
- Assists production of stain free, quality concrete finish.
- Protects timber forms against ingress of moisture, extending their useful life.
- Continued use gives progressively better results on timber formwork.
- Supplied ready to use; economically and easily applied by Adomast sprayers or other applicators.

Properties

Appearance: Light brown, low viscosity liquid.
Flash Point: 85°C
Freezing Point: -30°C
containers

Specific Gravity: 0.89 @ 20°C
Viscosity: 13.5 cSt @ 20°C
Storage Life: Indefinite in manufacturer's sealed

Application

Do not dilute; apply uniform coating to cleaned formwork surface avoiding excessive application. Apply as soon as possible after previous cast to give added protection from weather. Use FDI spray equipment, brush, swab, roller or squeegee, any excess should be mopped up. For new „unsealed“ timber forms pre-treatment is recommended with a second coat applied prior to use. This will extend the useful life of the form and help to standardise surface absorbency.

Coverage

25 to 45 m²/litre dependant upon type of form, porosity, texture of surface and ambient temperature.

Storage

FORMSTRIKE 402S in manufacturer's sealed drums require no special storage facilities. If spraying care should be taken to minimise inhalation and contact with eyes, ensure adequate ventilation during application.

Packaging

210 and 25 litre containers.

Health and Safety

FORMSTRIKE 402S is combustible. Avoid physical contact with material and inhalation. If contact with skin should occur wash with a suitable antiseptic cleaner and then soap and water. If splashes should affect eyes, bathe immediately with copious quantities of clean water and then immediately seek medical advice.

Reference should be made to the separate **FORMSTRIKE EXTRA 402S** Health and Safety literature.

formworkdirect.co.uk
TEL:
(+44) (0)151 532 0179
EMAIL
sales@formworkdirect.co.uk



formworkdirectmalta.com
TEL:
(+356) 9947 3031
EMAIL
sales@formworkdirectmalta.com