



FORMWORK TREATMENTS

Concrete Formwork Treatments

FORMTAPE

Description

A specially developed matt finish waterproof pressure-adhesive PVC tape. Available in two grades for use on all types of concrete formwork in climatic conditions ranging from cold to tropical.

Advantages

- Excellent adhesion even where residual release agent is present on form face.
- Retains flexibility at lower temperatures.
- Suitable for use at considerably higher ambient temperatures than conventional formwork tapes.
- Thinner, so as not to mark concrete.
- Suitable for use with all types of release agents.

Physical Data

Overall Thickness	0.14
Breaking Strength (N/cm width)	23
Adhesion to Steel (N/cm width)	1.3
Temperature Range	-100 to + 800°C

Application

Ensure surfaces are touch-dry. Apply to formwork prior to use of release agent but in the event of this not being possible wipe area as clean as possible. Apply **FORMTAPE** along the joint taking care not to cause any undue stretching so as to avoid any possible creep back. Press firmly on to surface and allow **FORMTAPE** to absorb any residual form release agent before pressure is re-applied to achieve maximum adhesion. The stability of the adhesive prevents sagging and distortion, even when used at high temperatures, unlike some tapes which are available.

Roll Dimensions

Width 50 mm Length 33 metres. 25 and 75 mm widths are available by special request.

Packaging

Carton 18 rolls Box 3 rolls

Colour

Grey (Yellow or white can be supplied if ordered in minimum quantities of 25 cartons).

Storage

Store at room temperature and protect from direct heat.

formworkdirect.co.uk
TEL:
(+44) (0)151 532 0179
EMAIL
sales@formworkdirect.co.uk



formworkdirect
International

formworkdirectmalta.com
TEL:
+356 2124 4241
EMAIL
formworkdirect@polidano-group.com