



FORMFIX

Resin Based Construction Materials

EPOFORM THIXOTROPIC FILLER

Description:

A blend of selected fine fillers that can be added to **EPOFORM** epoxy resins to produce a chosen workability.

Typical applications:

- Bedding mortars
- Repair mixes
- Caulking mixes

Advantages:

- Adjustable workability
- Fine grain size for thin sections

Typical data:

Grading:

122 µm	100%
54.7 µm	96.7%
24.6 µm	75.1%
10.3 µm	43.6%
4.97 µm	19.2%
2.99 µm	5.1%
1.93 µm	1.2%

Average (50%) 12.5m

Bulk density 820 Kg/m³

Acid solubility 4.60%

Water solubility 0.10%

PH 7.10

Instructions for Use:

EPOFORM THIXOTROPIC FILLER can be used with both **FORMTAC** and **FORMBOND** to produce progressively stiffer mixtures to suit a variety of applications.

Applications include filled adhesives, bedding and caulking mixes.
Mix the resin base according to the instructions on the pack.

Add **EPOFORM THIXOTROPIC FILLER** to the mixed resin and hardener base to adjust the consistency until the desired workability is achieved. When using in a very stiff form it is sometimes advisable to use some of the base pack as a primer/adhesive on the substrate before placing the filled mixture.

Only mix as much as can be used in 30 minutes (less at higher temperatures).

Clean tools with **RESOKLENS (FORMTAC)** or water (**FORMBOND**) before materials have set.

Storage:

Store in dry conditions and keep container sealed when not in use. Shelf life when stored correctly is in excess of 12 months.

Packaging:

4 and 12Kg bags.

Health and safety:

EPOFORM THIXOTROPIC FILLER has a high proportion of fine dust particles and the use of dust masks and goggles is recommended.

Refer to separate **EPOFORM THIXOTROPIC FILLER** Health and Safety sheet.

formworkdirect.co.uk
TEL:
(+44) (0)151 532 0179
EMAIL
sales@formworkdirect.co.uk



formworkdirectmalta.com
TEL:
+356 2124 4241
EMAIL
formworkdirect@polidano-group.com